Item #:

MENUMASTER[®] Commercial



Model DEC21E2 shown

Heavy Volume This category of microwave is ideal for...

Applications:

- Quick service restaurants
- Fast casual dining
- Bars & grills

Defrost:

- Defrosts most frozen food products

Heavy Volume

Menumaster Commercial Microwave Model DEC21E2

Power Output

- 2100 watts of power.
- 11 power levels for consistent, delicious results for frozen, refrigerated and fresh foods - from the freezer to table in minutes.
- Unique method of energy distribution provides superior even heating throughout the cavity.
- Interlock switch assembly is engineered for maximum durability and long life.

Easy to Use

- Up to 100 programmable menu items simplifies cooking and ensures consistent results.
- Four stage cooking option with one-touch programming. Reduces prep time, labor and food waste while providing consistent results.
- Controls are user friendly and require minimal training.
- Multiple quantity pad calculates the proper cook times for multiple portions.
- Ample 17 liter (.6 cubic ft.) capacity accommodates a standard half-sized pan.
- Stackable to save valuable counter space.
- Interior ceramic shelf is sealed and recessed to reduce plate-to-shelf edge impact and keep spills contained.

Easy to Maintain


- Stainless steel exterior and interior for easy cleaning and a professional look.
- Constructed to withstand the foodservice environment.
- Removable, cleanable air filter and clean filter reminder protects oven components.
- ETL Listed.





AIA File #:

Menumaster Commercial Microwave Model DEC21E2 | Heavy Volume



C

Specifications			
Model	DEC21E2 UPC Code 719881167718		
Configuration	Countertop		
Control System	Touch		
Programmable Control Pads	10		
Settings Programmable	100		
Max. Cooking Time	60:00		
Power Levels	11		
Defrost	Yes, power level 2		
Time Entry Option	Yes		
Microwave Distribution	Double rotating antennas, top and bottom		
Magnetrons	2		
Display	LED		
Stackable	Yes		
Stage Cooking	Yes, 4		
Door Opening	Grab and pull handle		
Signal	Adjustable, end of cycle		
Air Filter	Yes, removable, with clean filter reminder		
Multiple Portion Setting	Yes, up to 2 portions		
Exterior Dimensions	H 343 (13 ½")	W 419 (16 ½″)	D** 578 (22 ¾")
Cavity Dimensions	H 171 (6 ¾″)	W 330 (13″)	D 305 (12")
Door Depth	940mm (37″), 90°+ door open		
Usable Cavity Space	17 liter (.6 cubic ft.)		
Exterior Finish	Stainless steel		
Interior Finish	Stainless steel with sealed-in ceramic shelf		
Power Consumption	3100 W, 13.5 A		
Power Output*	2100 W* Microwave		
Power Source	230V, 50 Hz, 16 A single phase		
Plug Configuration / Cord	CEE 7/7 "Schuke	o" 1.7m (5' 6")	\bullet
Frequency	2450 MHz		
Product Weight	31 kg (68 lbs.)		
Ship weight (approx.)	34 kg (74 lbs.)		

L 625 (24 5/8")

Specifications

Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items and shall have automatic cooking capability for up to two portions. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. LED display shall be a backlit. There shall be 11 power levels, 4 cooking stages and defrost mode at 20% power or power level 2. Microwave output shall be 2100 watts distributed by two magnetrons each with a rotating antenna to provide superior even heating throughout the cavity. Heavy duty door shall have a tempered glass outer window and a grab and pull handle with 90°+ opening for easy access. The large 17 liter (6 cubic ft.) cavity shall accommodate a standard 152 mm (6") deep half-sized pan. Interior ceramic shelf shall be sealed and recessed on oven bottom to reduce plate-to-shelf edge impact. Oven shall have a stainless steel interior and exterior and be stackable to save counter and shelf space. Oven shall have removable, cleanable splatter shield. Air filter shall be easily accessible and removable from the front of the oven and have a "clean filter" reminder feature. Microwave oven shall comply with standards set by the U.S Department of Health and Human Services, ETL for safety.



Warranty Warranty Certificate for this product can be found by locating it on the ACP, Inc. website at:

www.acpsolutions.com/warranty



AIA File #:

Measurements are in millimeters

* IEC 60705 Tested

Shipping Carton Size

** Includes handle



W 556 (21 ⁷/₈") D 473 (18 ⁵/₈")

225 49th Ave. Dr. SW Cedar Rapids, IA 52404 U.S.A.

800-233-2366 319-368-8120 Product of the U.S.A. Fax: 319-368-8198 © 2013 ACP Inc.™

Drie

www.acpsolutions.com